

AZD-AZD-AZDMUC3317-F2X_F3X Rear axle final drive suspension; VIN: XXXXXXXX

ISTA system version	3.55.11.16402	Data version	R3.54	Programming	- data
VIN	XXXXXXX	Vehicle	2'/F22/Coupe/M235i/N55/AUTO/US/LL/2016/01		
Int.lev.works	-	Int.lev.(cur.)	-	Int.lev.(tar.)	-
Mileage	0 km				

33 17 Rear axle final drive suspension

	Type	Thread	Tightening specifications	Dimension
1AZ Rear differential to rear axle carrier, front	F20 / F21 / F22 / F23 / F30 / F31 / F32 / F33 / F34 / F35 / F36	M12	Follow repair instruction.	100 Nm
2AZ Rear differential to rear axle carrier, rear	F20 / F21 / F22 / F23 / F30 / F31 / F32 / F33 / F34 / F35 / F36	M14	Observe instructions in Repair Manual. Renew nut.	165 Nm
3AZ Vibration absorber to screw connection of rear axle differential, rear	F20 / F21 / F22 / F23 / F30 / F31 / F32 / F33 / F34 / F35 / F36	M8		28 Nm
4AZ Vibration absorber to rear axle support, rear	F20 / F21 / F22 / F23 / F30 / F31 / F32 / F33 / F34 / F35 / F36	M8		19 Nm
5AZ Vibration absorber to rear axle differential	F20 / F21 / F22 / F23 / F30 / F31 / F32 / F33 / F34 / F35 / F36	M12	Renew screw.	100 Nm
6AZ Vibration absorber to screw connection of rear axle differential, rear	F20 / F21 / F22 / F23 / F30 / F31 / F32 / F33 / F34 / F35 / F36	M10x32	Renew screw. Jointing torque Angle of rotation	56 Nm 90 °